

AKON



CURTAIN AND DIVIDER

www.curtain-and-divider.com

P: 989-414-1209 F: 888-501-5865

Style: 13-604

VINYL LAMINATED POLYESTER

TYPICAL PERFORMANCE PROPERTIES

Fabric Weight	2.7 oz./sq.yd.
Base Type	Polyester

Total Weight	
Method 5041	13 oz./sq.yd.

Grab Tensile	
Method 5100	250 x 225 lbs.

Strip Tensile	
Method 5102	150 x 140 lbs./in.

Tongue Tear	
Method 5134	70 x 80 lbs.

Adhesion, lbs/1 inch	
Heat Seal	20.0 lbs.

Puncture Resistance	
Method 2031, Fed.Std. 101C	170

Hydrostatic Resistance	
Method 5512	400 psi

—

Low Temperature
Mil-C-20696E, Par. 4.3.7

-40 Deg.C

Flame Resistance

Cal. Fire- Title 19

Pass

Method 5903

Pass

NFPA 701- small scale

Pass

FAR 25.853 (b)

Pass

We believe this

information is the best currently available, but assume no obligation or liability in connection therewith. We make no guarantee of results and no representation that the material is fit for any particular purpose. There are NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, unless specified in writing and signed by BondCote Corporation.