

# AKON



## CURTAIN AND DIVIDER

P: 989-414-1209 F: 888-501-5865

www.curtain-and-divider.com

Description: **LOW TEMP USDA**

### PRODUCT SPECIFICATIONS

<b>Roll Size</b>		
THICKNESS:	.040" to .250"	
WIDTH:	4" to 60"	
<b>Material Description</b>		
FINISH:	Double Polished	
COLOR:	Clear	
<b>Physical Properties</b>		
Property	Result	ASTM
Hardness (15 sec. delay)	70 A Scale	D2240
Tensile Strength:	2200 PSI	D412
Ultimate Elongation:	400%	D412
Graves Tear:	220 PPI	D1004
100% Modulus:	1000 PSI	D412
Stiffness: (-20°F)	-	-
Brittleness Temp:	-55° F	D746
Operating Temp:	-20° F to 140° F	-
Specific Gravity:	1.20	D792
Density:	75 lbs. cu.ft.	C-177
Thermal Conductivity (K):	.73	C-177
Thermal Resistance (R):	1.37	C-177
UV Resistance:	YES	
Flammability Rating:	Select Material Compliant with CA State Fire Marshal	
Shipped in a box on 6" cores		

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.